

Mediant™ 800 MSBR

Multi-Service Business Router

The AudioCodes Mediant™ 800 Multi-Service Business Router (MSBR) is an all-in-one router combining access, data, voice and security in a single device. It is ideal for managed data, SIP trunking, hosted PBX and cloud services, and allows service providers to deploy flexible and cost-effective solutions and to maximize revenue opportunities while minimizing CAPEX and OPEX.



Designed specifically to meet the needs of SMBs and SMEs, the Mediant™ 800 MSBR's unique multi-core architecture provides consistent high performance across all services, allowing end customers to get the most from their broadband connections for both data and voice applications.

4 WAN Interfaces | 124 TDM Sessions | 12 LAN Interfaces | Wi-Fi 802.11n



Comprehensive interoperability

Supports up to 4 E1/T1 trunks, analog phones, fax, PBX and PSTN connectivity; OSN server support for hosting third-party services



All-in-one functionality

Business router with access, data, voice and security in a single, cost-efficient platform



Multiple interfaces

LAN, WAN and Wi-Fi interfaces with powerful routing, switching and firewall



Superior quality

Consistent high performance with multi-core architecture



High resiliency

Survivability of data and telephony services in the event of a WAN failure

Specifications

Capacity			
	Max. Signaling/Media Sessions	Max. Registered Users	Transcoding Sessions
Mediant 800B	60	500	57
Mediant 800C	150	600	110
Networking Interfaces			
WAN	Multiple WAN support for T1/E1, SHDSL, ADSL2+, VDSL2 vectoring, 100Base-X, 1000Base-X (SFP Format)		
LAN	Up to 12 ports 10/100/1000Base-T with option for Power over Ethernet on all ports. (PoE 802.3 at up to 30W per port/200W total)		
Wi-Fi	Wi-Fi access point support for 802.11 a/b/g/n		
Telephony Interfaces			
Digital Interfaces	Up to 4 span E1/T1/J1 using RJ-48c connectors, 8 BRI ports using RJ-48c connectors with 5 PPM high precision clock source		
Analog Interfaces	Up to 12 analog FXS/FXO ports using RJ-11 connectors, option of 1 FXS lifeline port in case of power failure		
Voice Features			
Voice Coders	G.711, G.723.1, G.729A, G.722, AMR-WB, AMR-NB, SILK-NB, SILK-WB, OPUS-NB, OPUS-WB		
Echo Cancellation	G.165 and G.2002-168, with 64 ,32 or 128 msec tail length		
Fax Transport	T.38 compliant (real time fax), automatic bypass to PCM		
Data Routing			
	<ul style="list-style-type: none"> • PPP, MLPPP, PPPoE, PPPoA, L2TP, IPoE, IPoA • OAM-F5 (send/receive): loopback, continuity check • DHCP client, relay, server • VLAN and IEEE 802.1Q VLAN tagging • Layer 3 routing and layer 2 bridging, jumbo frames • Internal layer 2 switching • Static and dynamic routing (RIP1, RIP2, OSPFv2, BGP), policy-based routing • Multicast routing: IGMPv2 • IPv6, IPv6/IPv4 Dual Stack, ICMPv6, DHCPv6, SLAAC 		
Control and Management			
Control Protocols	<ul style="list-style-type: none"> • SIP-TCP, SIP-UDP, SIP-TLS and IPv6 supported 		
Operations & Management	<ul style="list-style-type: none"> • AudioCodes' One Voice Operation Center • Embedded HTTP Web Server, SNMP V2/V3, SSH, Telnet, TR-69,TR-098, TR-181,TR-104 • User authentication and access control via HTTP or HTTPS, RADIUS, TACACS, Syslog (for events and alarms) • Zero Touch Provisioning 		
Quality of Service			
	<ul style="list-style-type: none"> • IEEE 802.1P, DSCP, TOS, DiffServ labeling, WRED • Marking, policing, and shaping, class-based queuing with prioritization, queuing based on VLAN 		
Security			
Voice Security - Session Border Controller (SBC)	<ul style="list-style-type: none"> • SIP header conversion, SIP normalization • Survivability • IP-to-IP routing translations of various SIP transport types; UDP, TCP, TLS, translation of RTP, SRTP • Support SIP trunk with multi-ITSP (registrations to ITSPs are invoked independently) • Topology hiding • Call Admission Control • Call black/white list 		
Data Security	<ul style="list-style-type: none"> • IPsec • ESP – Tunnel mode • Encryption protocols: 3DES, AES, SHA-256, MD-5 • IDS/IPS (fragmented traffic, malformed request, ping of death, properly formed request from unauthenticated source, DDoS attack, SYN flood) • Stateful packet inspection firewall • DMZ host • Packet filtering • Network Access Control - 802.1x 		
Physical/Environmental			
Dimensions	1U x 320mm x 345mm (HxWxD)	Weight	Approx. 5.95lb (2.7kg) loaded with OSN
Mounting	Desktop or 19" rack mount	Operating Temperature	5°-40° C
Power	Mediant 800B	Internal AC power supply rated: 100-240V 4A 50- 60 Hz	
	Mediant 800C	Internal AC power supply rated: 100-240 VAC ~50- 60Hz 1.5A maximum (Optional) Additional 12V 10A DC power, via an AudioCodes external AC/DC power adaptor	
OSN Server Platform (Optional)			
Single Chassis Integration	Optional embedded, x86, Intel-based Open Solution Network platform for third-party applications		



International Headquarters
 1 Hayarden Street, Airport City
 Lod 7019900, Israel
 Tel: +972-3-976-4000
 Fax: +972-3-976-4040

AudioCodes Inc.
 27 World's Fair Drive,
 Somerset, NJ 08873
 Tel:+1-732-469-0880
 Fax:+1-732-469-2298

Contact us: www.audiocodes.com/contact
 Website: www.audiocodes.com

©2018 AudioCodes Ltd. All rights reserved. AudioCodes, AC, HD VoIP, HD VoIP Sounds Better, IPmedia, Mediant, MediaPack, What's Inside Matters, OSN, SmartTAP, User Management Pack, VMAS, VoIPerfect, VoIPerfectHD, Your Gateway To VoIP, 3GX, VocaNom, AudioCodes One Voice and CloudBond are trademarks or registered trademarks of AudioCodes Limited. All other products or trademarks are property of their respective owners. Product specifications are subject to change without notice.